

ARP 75

PIVOT-STEER TANDEM ROLLER

EU STAGE V / U.S. EPA TIER 4 FINAL



APPLICATIONS

- Medium and large compaction projects
- Transport construction: highways, municipal roads, airfields
- Industrial zones
- Parking areas
- Downtowns

PRODUCTIVITY

Variable compaction output

Two-stage vibratory system enables adjustment to the particular jobsite.

Smooth rolling

Advanced drive system prevents sudden starts and stops during machine operation.

ERGONOMICS

Platform and cab

Spacious and quiet, with 360° visibility.

Operator station

Provides high comfort and safety.

SERVICEABILITY

Minimized downtime

Heavy duty components and robust construction.

Reduced maintenance

Extended service intervals; easy-to-reach maintenance points.

SUSTAINABILITY

ECODrop

Improved efficiency, reduced use of fluids.

Advanced technologies

Including monitoring and measuring systems, enhance efficiency, productivity, and enable precise documentation.

OPTIONAL EQUIPMENT

- A/C
- Additional documentation printed
- Additional lights 360° LED
- Additional lights cab LED
- Ammann Documentation Syst. ADS
- Ammann Documentation Syst. ADS RTK
- AmmannCare Silver
- AmmannCare Gold
- AmmannCare Platinum
- AmmannCare Diamond
- Back-up alarm
- Back-up alarm adaptive
- Certificate of origin
- Color scheme customer
- Cooling box
- Drum steps foldable front/rear
- Edge cutter 45° (diagonal)
- Edge cutter 45° (front right)
- Edge cutter 45° (rear left)
- Engine automatic stop
- Fire extinguisher
- GPS Q-Compaction ACE
- GPS Q-Compaction Preparation ACE
- Hydraulic oil biodegradable
- Chip spreader Ammann
- Chip Spreader Disc
- Chip spreader Preparation
- Infrared thermometer
- Maintenance Kit 2000h
- Maintenance Kit 1000h
- Maintenance Kit 500h
- Radio DAB
- Rear view camera
- Registration plate holder incl. light
- eROPS
- Slow moving vehicle triangle
- Sun films on cab glasses
- Sun visor
- Telematics Preparation
- Telematics ServiceLink Plus
- Telematics ServiceLink Pro
- Toolset
- Transport remote control
- Warning beacon green LED
- Warning beacon LED
- Water tank filling from ground


STANDARD EQUIPMENT

- Ammann color design and decals
- Ammann Traction Control - ATC
- Battery disconnection switch
- Cab ROPS
- Centralized draining points
- Double drum version: Front and rear drive and vibration
- Double drum version: Two split steerable drums
- ECODrop
- Electronic drive lever with intelligent functions
- FTS (Finger-Tip-Steering)
- Multi-functional 10inch touchable display for machine control and overview
- On-board diagnostics
- Operator's station with one drive lever (RH)
- Pressure water sprinkling with interval switch, 3 stage filtration and 2 pumps
- Road lights (headlights, rearlights, turning signals, brake lights)
- Slideable, 270° rotatable and horizontally adjustable driver's seat with armrests
- Standard hydraulic oil
- Tilttable scrapers
- Variable working width (Off-set steering modes)
- CE conformity
- Compaction measuring system ACE^{Pro}
- Telematics Readiness

AMMANN

ARP 75

StV / T4f



WEIGHT & OPERATING CHARACTERISTICS

	ARP75 ACE ^{pro}
OPERATING WEIGHT	7 610 kg (16 777 lb)
OPERATING WEIGHT MAX.	8 990 kg (19 820 lb)
STATIC LINEAR LOAD AVG.	25.1 kg/cm (140.6 lb/in)
MAX. WORKING SPEED	10 km/h (6.2 MPH)
GRADEABILITY WITHOUT VIBRATION	30%
GRADEABILITY WITH VIBRATION	25%
TURNING RADIUS (INNER)	2 940 mm (115.7 in)
DRUM OFFSET	1 220 mm (48 in)

COMPACTION FORCES

	ARP75 ACE ^{pro}
FREQUENCY	38–55 Hz (2 280–3 300 vpm)
CENTRIFUGAL FORCE	83 kN (18 659 lbf)
AMPLITUDE	0.87 mm (0.034 in)

ENGINE

MANUFACTURER	Kubota
ENGINE TYPE	V3307-CR-T
ENGINE SPEED	2400 rpm
POWER OUTPUT SAE J1995	55.4 kW / 74HP
EMISSION STAGE	EU Stage V
EXHAUST GAS AFTER-TREATMENT	EGR+DOC+DPF

MISCELLANEOUS

BRAKES OPERATING	Hydrostatic
BRAKES PARKING	Multiple-disc spring brake
BRAKES EMERGENCY	Multiple-disc spring brake
FUEL TANK CAPACITY	160 l (42.3 gal)
WATER TANK CAPACITY	900 l (237.8 gal)
TYPE OF WATERING	Pressure
HYDRAULIC TANK CAPACITY	84 l (22.2 gal)
STEERING ANGLE	±24°
OSCILLATION ANGLE	±4°
BATTERY VOLTAGE	12V
BATTERY CAPACITY	120 Ah

MAXIMUM RECOMMENDED COMPACTED LIFT THICKNESS AT OPTIMAL WORKING CONDITIONS

ROCKFILL	–
SAND / GRAVEL	350 mm (13.8 in)
MIXED SOILS	250 mm (9.8 in)
SILT	–
CLAY	–
STABILISATION	180 mm (7.1 in)
ASPHALT	130 mm (5.1 in)

ARS 75 StV 

For additional product information and services please visit: www.ammann.com
Materials and specification data are subject to change without notice.
MSS-3378-00-EN | © Ammann Group

AMMANN