

Technical data: for UX Super trailed sprayers

Model: UX Super	4201	5201	6201	7601	8601	11201
Nominal tank capacity (l)	4,200	5,200	6,200	7,600	8,600	11,200
Actual tank capacity (l)	4,600	5,600	6,560	8,000	9,030	12,000
Fresh water tank capacity(l)	580					900
Internal tank cleaning system	Standard					
SmartCenter	Standard-Pack					
	Comfort-Pack					
	Comfort-Pack plus					
DirectInject	only with Comfort-Pack plus					
Xtreme-Clean	only with Comfort-Pack or Comfort-Pack plus					
Storage compartment (l)	240					
Induction bowl capacity	60 l with large storage space, rinse ring, canister rinse nozzle, mixing nozzle and hand lance					
Suction rate of induction bowl (l/min)	200					
Pump capacity (l/min)	520 (260 + 260)			650 (300 + 350)		700 (350 + 350)
Max. suction capacity (l/min)	700			800		900
Pump drive	mechanical or hydraulic					
max. flow rate when spraying – standard	200 l/min (at a spray pressure of 1 to 10 bar)					
max. flow rate when spraying with HighFlow ⁺	400 l/min (at a spray pressure of 1 to 10 bar) only with Comfort-Pack or Comfort-Pack plus					
Straight drawbar – top mounted	rigid					
Hitch drawbar – lower mounted	rigid					
Drawbar shock absorbance system	Standard					Standard
Parking jack	hydraulic					
Towing eyes	Option					
Axles	Adjustable axle					
	rigid – 2,000 mm		rigid – 2,100 mm			
	steered up to 15° – 1,800 mm					
	steered up to 20° – 2,000 mm					
	steered up to 28° – 2,100 mm					
Axle suspension, passive				Option		
Axle suspension, active – hydro-pneumatic	Option			Option		Standard
Track widths (m)	1.50–2.25	1.80–2.25	2.00–2.25	1.80–2.25		2.00–2.25
min. tyre size (diameter)	270/85 R48 (Ø 1,740 mm)	300/95 R52 (Ø 1,890 mm)	480/80 R46 (Ø 1,936 mm)	380/90 R46 (Ø 1,842 mm)		
max. tyre size (diameter)	620/70 R46 (Ø 2,050 mm)			710/75 R42 (Ø 2,140 mm)		520/85 R42 (Ø 1,950 mm)
	further tyre options on request					
Braking systems	Hydraulic braking system / pneumatic braking system – depending on national regulations!					
ALB	Standard in conjunction with a pneumatic braking system					
Axle steering	AutoTrail axle steering only in conjunction with steered axle					Single- / Double-Trail
Automatic slope compensation	Standard in conjunction with AutoTrail axle steering					
External wash kit	Option					
Underbelly covers	Option					
Transport height (m)	3.52–3.79		3.75–3.90	3.65–3.80	3.75–3.90	3.90
Transport length (m)	6.85–7.30		7.05–7.50	7.95–8.10		9.70
Unladen weight (from kg)	4,044	4,089	4,274	4,828	4,978	8,054
Working widths (m)	21–48					30–48
Spraying height (m)	approx. 0.5–2.5 m depending on the tyres					
max. working pressure (bar)	10					

 = Standard

 = Option

 = Selection

Booms

for UX Super trailed sprayers

Boom type	Super-L2														Super-L3									
Working widths (m)	21	24	27	27	27	28	28	30	32	33	33	36	36	30	33	36	39	40	42	45	48			
possible reduced working widths	15	19	19	21	19	22	24	26	26	26	27	28	30	24	24	24	33	33	33	35	36			
	9	10	10	15	10	15	15	19	19	19	21	19	24	12	12	12	24	24	24	24	24			
				8		8	8	10	10	10	12	10	12				12	12	12	12	12			
UX 4201, UX 5201, UX 6201, UX 7601, UX 8601																								
UX 11201																								
1-, 3-, 4-fold without DUS																								
1-, 3-, 4-fold with DUS																								
AmaSwitch plus 3-fold, DUS pro, 50 cm																								
AmaSwitch plus 4-fold, DUS pro, 50 cm / 25 cm (option)																								
AmaSelect, DUS pro, 50 cm / 25 cm (option)																								
Boom fold	Number of spool valves																							
Profi-fold 1	1 single-acting and free flow return / Load-Sensing																							
Flex-fold 1	1 single-acting and free flow return / Load-Sensing																							
Flex-fold 2	1 single-acting and free flow return / Load-Sensing																							
Boom guidance	Number of sensors for boom guidance																							
DistanceControl	2 (Profi-fold 1, Flex-fold 1 & 2)																							
DistanceControl plus	4 (Profi-fold 1, Flex-fold 1 & 2)																							
ContourControl	4 (Flex-fold 1), 6 (Flex-fold 2)																							
ContourControl with SwingStop	4 (Flex-fold 1), 6 (Flex-fold 2)																							
ContourControl with SwingStop plus																	6 (Flex-fold 2)							
Boom lighting																								
LED work lights	Option																							
LED individual nozzle lighting	Option / Standard with AmaSelect																							

Operation / Terminal	ISOBUS
ISOBUS software	Standard
GPS-Switch	Option
GPS-Maps	Option
GPS-Track	Option
Other AmaSelect functions	
AmaSelect HeightSelect automatic height adjustment	Standard
AmaSelect CurveControl curve compensation	Standard for AmaSelect with ContourControl
AmaSelect Row band application	Option
AmaSelect Spot spot application	Standard

■ = Standard

■ = Option / Standard

■ = Option

■ = Selection

Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required. The permissible axle loads and total weights of the tractor should be checked. Not all the listed combination options are possible with all tractor manufacturers.

The smaller alternatives – The UX Special and UG trailed sprayers

For smaller farms, AMAZONE offers the UX Special and UG trailed sprayers with tank capacities from 2,200 to 5,200 litres. Further information can be found in the machine specific brochures.